

## Fluid refrigerators for laser source

### SLIM SERIES



MODEL			RSN901	RSN132	RSN202	RSN302	RSN352
<b>TECHNICAL DATA</b>							
Cooling capacity		kW	0.9	1.3	2	3	3.5
Fluid tank		ltr.	4	4	4	6.5	6.5
Fluid delivery		mca	40	40	40		30
		l/min	5	5	5	6	6
Air flow to the condenser		m <sup>3</sup> /h	500	800	1100	2500	2500
Noise level	(minore)	dB(A)	60	60	65	66	66
Refrigerant		R	134a	134a	404a	404a	404a
Height		mm	560	652	652	780	780
Width		mm	420	233	233	435	435
Depth		mm	220	510	510	560	560
Weight		kg	33	39	42	58	60
Electrical protection		IP	41	43	43	43	43
<b>ELECTRIC DATA</b>							
Total power absorption	(winter/summer)	W	700	920	1130	2300	2520
Power supply		V/Ph/Hz	220/1/50-60	220/1/50-60	220/1/50-60	220/1/50-60	220/1/50-60
<b>FUNCTIONAL LIMITS</b>							
External temperature	Min./Max	°C	10/45	10/45	10/45	10/45	10/45
Water temperature	Min./Max	°C	20/35	20/35	20/35	20/35	20/35
Performance referred to:	Ambient temperature	°C	25	25	25	25	25
	Conditioned area temperature	°C	25	25	25	25	25